

tesa® 52664

Plate mounting in flexographic printing, especially corrugated board postprint

PRODUCT INFORMATION

Product Description

tesa® 52664 consists of a tear resistant flexible fabric backing, with a rubber adhesive system. The adhesive has a high coating weight making it well suited to mounting plates in flexographic printing applications, especially in corrugated board postprint. High adhesion and backing strength also ensure secure vertical storage of mounted plates.

tesa® 52664 can be removed easily without leaving adhesive residues.

- · High adhesion values for reliable application, even when the composite is stored vertically for longer periods
- · High adhesion and shear also ensure that there is no edge lifting, even on longer print runs and at higher speeds

Backing

• Cloth backing for excellent, reliable bond, even when stored vertically.

Main Application

tesa® 52664 is especially well suited to plate mounting in corrugated board postprint, due to its ideal adhesive characteristics and optimal backing properties.

Technical Data

- Backing material
- cloth
- Type of adhesive
- natural rubber

- Thickness category
- 380 µm
- Type of liner
- glassine

For latest information on this product please visit http://l.tesa.com/?ip=52664

Page 1 of 1 / As of 12/01/13

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707 Phone: +65 (68) 612 026

tesa tape inc.

tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle, Singapore 629621

Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.